IOWA DEPARTMENT OF NATURAL RESOURCES NPDES PERMIT APPLICATION FORM 3 FOR INDUSTRIAL FACILITIES

FORM 3 - FACILITIES WHICH DISCHARGE PROCESS WASTEWATER - EXISTING SOURCES

Outfall No.	Operation	Fl	ow	Fred	uency	Duration
zatran 1 (o.	operation	avg	max	days/week	months/year	(in days)
-						
eceiving Stream Na	me:	<u> </u>			L	
eeer ing stream i te						
					-	
eceiving Stream Na	me:	<u> </u>			L	
				1		

Facility Name:					
II Duoduotion					
II. Production	fodoral offluent guidaline promulgated under Section 20	M of the Cl	oon Wat	on A at?	
Yes	federal effluent guideline promulgated under Section 30 No If "yes" list 40				
	t guidelines expressed in terms of production? (See Tabl	_			
Yes	No	e i oi the i	nsti uctio	115)	
	• Item IIB list the quantity or quantities which represent	vour actus	al produc	rtion evnress	ed in the same
terms as applicable.	tem 11D list the quantity of quantities which represent	your actua	ar produc	cuon express	eu in the same
Quantity Per Day	Operation, Product, Raw Material			Units	
III. Effluent Characteristics					
	own in Table 2 of the instructions which you know or have For each pollutant you list, briefly describe the reasons				
Pollutant	Source	Concer	tration	Outfall	Certified
1 onuture	Source	avg	max	Guillin	Laboratory
		(mg/l)	(mg/l)		Number
		(8/-)	(
(1) The name of the manufactories(1) Sheet (MSDS).(2) The concentration of the	microbiocides, cooling water or boiler chemicals) you noturer of each chemical used and list their composition of chemical additive estimated to be discharged in ppm or formation of the chemical if available. Specifically, the MSDS.	or provide a	a copy of	each Materia	al Safety Data
Attach additional sheets if nec	essary.				
IV. Toxicity Test Data					
If any biological test for acut the test(s), their purpose(s) a	e or chronic toxicity has been conducted on any of your nd the $\mbox{result}(s)$.	discharges	within tl	he past three	years describe
Attach additional sheets if nec	essary.				

Facility Name:									Outfall Nu	ımber:		
V. EFFLUENT CHARACT	FERIST	ICS										
Part A - You must provide th	he result	s of at le	ast one analy	sis for every	pollutant in t	his table. Con	nplete one tal	ble for each o	utfall. See in	structions fo	r additiona	ıl details
_		-			-	B. EFFLUENT	Γ		-	4. UN	NITS	5. CERTIFIED
			MAXIMUM D	AILY VALUE	MAXIMUM 30	DAY VALUE	LONG TERM	AVG. VALUE	NO. OF	(specify i	f blank)	LABORATORY
1. POLLUTANT					(if avai	ilable)	(if avai	ilable)	ANALYSES			NUMBER
			Concentration	Mass	Concentration	Mass	Concentration	Mass		Concentration	Mass	
a. Biochemical Oxygen Demand (BOD	D)											
b. Chemical Oxygen Demand (COD)												
c. Total Organic Carbon (TOC)												
d. Total Suspended Solids (TSS)												
e. Ammonia (as N)												
f. Flow											MILLION G.	ALLONS
											PER D	
g. Temperature											DEGRE	EES
(October - March)											FARENI	
h. Temperature											DEGRI	
(April – September) i. pH			Minimum	Maximum	Minimum	Maximum					FARENI STANDARI	
i. pii			14111111111111	Maximum		Maximum					STANDARL	ONIIS
Part B – Mark "X" in Colu	ımn 2A	for each	pollutant vo	u know or h	ave reason to	helieve is ni	esent. Mark	"X" in Colu	mn 2B for ea	L Ich pollutan	t vou believ	ve to be absent.
You must mark believed pr												
of at least one analysis for t												
presence in your discharge	_		_		~			_	_			
P-one-orange	F					B. EFFLUENT		1		4. UN	NITS	5. CERTIFIED
	2. MAF	K "X"	MAXIMUM D	AILY VALUE	MAXIMUM 30		LONG TERM	AVG. VALUE	NO. OF	(specify i		LABORATORY
1. POLLUTANT	Believed	Believed			(if ava	ilable)	(if avai	ilable)	ANALYSES			NUMBER
11 0220 1111 (1	Present	Absent	Concentration	Mass	Concentration	Mass	Concentration	Mass		Concentration	Mass	TOMBER
a. Bromide												
b. Chlorine, Total Residual												
c. Color												
d. Escherichia coli (E. coli)												
e. Fluoride												
f. Nitrate-Nitrite (as N)												

Facility Name:									Outfall Nu	ımber:		
					3	. EFFLUENT	Γ			4. UN	NITS	5. CERTIFIED
	2. MA	RK "X"	MAXIMUM D	AILY VALUE	MAXIMUM 30		LONG TERM	AVG. VALUE	NO. OF	(specify i	if blank)	LABORATORY
1. POLLUTANT	Believed	Believed			(if avail	lable)	(if ava	ilable)	ANALYSES			NUMBER
	Present	Absent	Concentration	Mass	Concentration	Mass	Concentration	Mass		Concentration	Mass	1,61,2221
g. Nitrogen Total Organic (as N)												
h. Oil and Grease												
i. Phosphorus, Total (as P)												
j. RADIOACTIVITY					<u> </u>							
(1) Alpha, Total												
(2) Beta, Total												
(3)Radium, Total												
(4) Radium 226, Total												
k. Sulfate (as SO4)												
1. Sulfide (as S)												
m. Sulfite (as SO3)												
n. Surfactants												
o. Aluminum, Total												
p. Barium, Total												
q. Boron, Total												
r. Cobalt, Total												
s. Iron, Total												
t. Magnesium, Total												
u. Molybdenum, Total												
v. Manganese, Total												
w. Tin, Total												
x. Titanium, Total												

Facility Name:										Outfal	l Number:	$\overline{}$	
Part C – If you ar	e an industr	v listed in Ta	able 1 of the i	instructions,	and this out	fall contains	process was	stewater, re	fer to Table 1			termine v	vhich of the
													nols. If you are not
required to mark													
													ults of at least one oncentrations of 10
ppb (µg/l) or grea													
each of these poll	itqants whic	h you know	or have reas	on to believe	that you dis	charge in co	ncentration	s of 100 ppb	or greater. (Otherwise, fo	r pollutants	for which	ı you marked
											hat there are	seven (7)) pages to this part
please review eacl	n carefully. (complete on	e table (all 7	pages) for ea	ch outfall. S	ee instruction	ons for addit	ional detail	s and require	ments.			
					EFFLUEN'					NO. O	4. UN	ITS	5. CERTIFIED
		2. MARK "X		MAXIMUM D	AILY VALUE			Į.	AVG. VALUE	ANALYSES	(specify if	blank)	LABORATORY
1. POLLUTANT	a. TESTING REQUIRED	b. BELIEVED PRESENT	c. BELIEVED ABSENT	Concentration	Mass	(if ava	ntration	, ,	vailable) Mass		Concentration	Mass	NUMBER
METALS, CYA				Concentration	Mass	Concer	iti auon	I.	/1855		Concentration	IVIASS	-
1M. Antimony, Total													
2M. Arsenic, Total												 	
	Ш											<u> </u>	
3M. Beryllium, Total													
4M. Cadmium, Total													
5M. Chromium, Total													
6M. Copper, Total													
7M. Lead, Total													
8M. Mercury, Total													
9M. Nickel, Total													
10M. Selenium, Total													
11M. Silver, Total													
12M. Thallium, Total													
13M. Zinc, Total													
14M. Cyanide, Total													
15M. Phenols, Total													
DIOXIN						•		•	•	•			
2,3,7,8-Tetra-				DESCRIBE	RESULTS								
chlorodibenzo-P- Dioxin													

Facility Name:									(Outfall Num	ber:		
·						3. EFF	LUENT			NO. OF	4. UN	ITS	5. CERTIFIED
1. POLLUTANT		2. MARK "X b. BELIEVED		MAXIMUM DA	AILY VALUE	MAXIMUM 30		LONG TERM		ANALYSES	(specify if	blank)	LABORATORY NUMBER
	REQUIRED	PRESENT	ABSENT	Concentration	Mass	Concentration	Mass	Concentration	Mass		Concentration	Mass	_
GC/MS FRACT	ION – VOL	ATILE OR	GANICS										-
1V. Acrolein													
2V. Acrylonitrile													
3V. Benzene													
4V. Bromoform													
5V. Carbon Tetrachloride													
6V. Chlorobenzene													
7V. Chlorodi- bromomethane													
8V. Chloroethane													
9V. 2-Chloro- ethylvinyl Ether													
10V. Chloroform													
11V. Dichloro- bromomethane													
12V. 1,1-Dichloro- ethane													
13V. 1,2-Dichloro- ethane													
14V. 1,1-Dichloro- ethylene													
15V. 1,2-Dichloro propane													
16V. 1,3-Dichloro- propylene													
17V. Ethylbenzene													
18V. Methyl Bromide													
19V. Methyl Chloride													
20V. Methylene Chloride													
21V. 1,1,2,2 Tetrachloroethane					_								

Facility Name:									(Outfall Num	ber:		
		•				3. EFFL	UENT			NO. OF	4. UN	ITS	5. CERTIFIED
1. POLLUTANT		2. MARK ''X		MAXIMUM DA	AILY VALUE	MAXIMUM 30			AVG. VALUE	ANALYSES	(specify if	blank)	LABORATORY
		b. BELIEVED	l			(if avail	-		ilable)				NUMBER
	REQUIRED	PRESENT	ABSENT	Concentration	Mass	Concentration	Mass	Concentration	Mass		Concentration	Mass	
		1						1					
22V. Tetrachloro- ethylene													
23V. Toluene													
24V. 1,2-Trans- Dichloroethylene													
25V. 1,1,1-Tri- chloroethane													
26V. 1,1,2-Tri- chloroethane													
27V. Trichloro- ethylene													
28V. Vinyl Chloride													
GC/MS FRACT	ION - ACID	COMPOU	NDS										
1A. 2-Chlorophenol													
2A. 2,4-Dichloro- pheno													
3A. 2,4-Dimethyl- phenol													
4A. 4,6-Dinitro-O- Cresol													
5A. 2,4-Dinitro- phenol													
6A. 2-Nitrophenol													
8A. P-Chloro-M- Cresol													
9A. Pentachloro- phenol													
10A. Phenol													
11A. 2,4,6-Tri- chlorophenol													
GC/MS FRACT	ION - BASE	E/NEUTRAI	L COMPOU	NDS	1			1					
1B. Acenaphthene													
2B. Acenaphtylene													
3B. Anthracene													

Facility Name:									(Outfall Num	ber:		
						3. EFFL	UENT			NO. OF	4. UN	ITS	5. CERTIFIED
1. POLLUTANT	a. TESTING	2. MARK "X b. BELIEVED		MAXIMUM DA	AILY VALUE	MAXIMUM 30 I		LONG TERM		ANALYSES	(specify if	blank)	LABORATORY NUMBER
	REQUIRED	PRESENT	ABSENT	Concentration	Mass	Concentration	Mass	Concentration	Mass		Concentration	Mass	-
GC/MS FRACT	ION – BAS	L/NEUTRA	L COMPOI	INDS									
4B. Benzidine													
5B. Benzo (a) Anthracene													
6B. Benzo (a) Pyrene													
7B. 3,4-Benzo- fluoranthene													
8B. Benzo (ghi) Perylene													
9B. Benzo (k) Fuoranthene													
10B. Bis (2-Chlor- ethoxy) Methane													
11B. Bis (2-Chloro Ethyl Ether													
12B. Bis (2-Chloroiso- propyl) Ether													
13B. Bis (2-ethyl- hexyl) Phthalate													
14B. 4-Bromo- phenyl Phenyl Ether													
15B. Butyl Benzyl Phthalate													
16B. 2-Chloro- naphthalene													
17B. 4-Chloro- phenyl Phenyl Ether													
18B. Chrysene													
19B. Dibenzo (a,h) Anthracene													
20B. 1,2-Dichloro benzene													
21B. 1,3-Dichloro- benzene													
22B. 1,4-Dichloro- benzene													
23B. 3,3'-Dichloro benzidine													
24B. Diethyl Phthalate													
25B. Dimethyl Phthalate													

Facility Name:										Outfall Num	ber:		
						3. EFFL	UENT			NO. OF	4. UN	ITS	5. CERTIFIED
1. POLLUTANT		2. MARK "X	"	MAXIMUM DA	AILY VALUE	MAXIMUM 30	DAY VALUE	LONG TERM	AVG. VALUE	ANALYSES	(specify if	blank)	LABORATORY NUMBER
	a. TESTING	b. BELIEVED	c. BELIEVED			(if availe	able)	(if avai	ilable)				NUMBER
	REQUIRED	PRESENT	ABSENT	Concentration	Mass	Concentration	Mass	Concentration	Mass		Concentration	Mass	
26B. Di-N-Butyl Phthalate													
27B. 2,4-Dinitro- toluene													
28B. 2,6-Dinitro- toluene													
29B. Di-N-Octyl Phthalate													
30B. 1,2-Diphenyl- hydrazine													
31B. Fluoranthene													
32B. Fluorene													
33B. Hexachloro- benzene													
34B. Hexachloro- butadiene													
35B. Hexachloro- cyclopentadiene													
36B. Hexachloro- ethane													
37B. Indeno- (1,2,3- cd) Pyrene													
38B. Isophorone													
39B. Naphthalene													
40B. Nitrobenzene													
41B. N-Nitro- sodimethylamine													
42B. N -Nitrosodi- N- Propylamine													
43B. N-Nitro- sodiphenylamine													
44B. Phenanthrene													
45B. Pyrene													
46B. 1,2,4-Tri- chlorobenzene													

Facility Name:										Outfall Num	ber:		
						3. EFFL				NO. OF	4. UN	ITS	5. CERTIFIED
1. POLLUTANT		2. MARK "X		MAXIMUM DA	AILY VALUE	MAXIMUM 30 I		LONG TERM	AVG. VALUE	ANALYSES	(specify if	blank)	LABORATORY
		b. BELIEVED	c. BELIEVED			(if availe	able)	(if avai	ilable)				NUMBER
	REQUIRED	PRESENT	ABSENT	Concentration	Mass	Concentration	Mass	Concentration	Mass		Concentration	Mass	
GC/MS FRACT	ION - PEST	TICIDES		L						L			
1P. Aldrin													
7P. 4,4'-DDT													
8P. 4,4'-DDE													
9P. 4,4'-DDD													
10P. Dieldrin													
11P. Alpha- Endosulfan													
12P. Beta-Endosulfan													
13P. Endosulfan Sulfate													
14. Endrin													
15P. Endrin Aldehyde													
16P. Heptachlor													
17P. Heptachlor Epoxide													
18P. PCB-1242													
19P. PCB-1254													
20P. PCB-1221													
21P. PCB-1232													
22P. PCB-1248													
23P. PCB-1260													
24P. PCB-1016													
25P. Toxaphene													

DO NOT SUBMIT THESE PAGES – FOR APPLICANT USE ONLY FORM 3 – INSTRUCTIONS FACILITIES THAT DISCHARGE PROCESS WASTEWATER – EXISTING SOURCES

Item I

List all sources of wastewater discharged through each outfall. Operations may be described in general terms (for example, "dye-making reactor" or "distillation tower"). You may estimate the flow contributed by each source if no data are available. For storm water discharges you may estimate the average flow, but you must indicate the rainfall event upon which the estimate is based and the method of estimation.

Item IIA

All effluent guidelines promulgated by EPA appear in the Federal Register and are published annually in 40 CFR Subchapter N. A guideline applies to you if you have any operations contributing **process** wastewater in any subcategory covered by a BPT, BCT, NSPS, or BAT guideline. You must check "yes" if an applicable effluent guideline has been promulgated, even if the guideline limitations are being contested in court. If you believe that a promulgated effluent guideline has been remanded for reconsideration by a court and does not apply to your operations, you may check "no".

Item IIB

An effluent guideline is expressed in terms of production (or other measure of operation) if the limitation is expressed as mass of pollutant per operational parameter; for example, "pounds of BOD per cubic foot of logs from which bark is removed," or "pounds of TSS per megawatt hour of electrical energy consumed by smelting furnace". An example of a guideline not expressed in terms of a measure of operation is one which limits the concentration of pollutants.

Item IIC

This item must be completed only if you checked "yes" to item II.B. The production information requested here is necessary to apply effluent guidelines to your facility. Report quantities in the units of measurement used in the applicable effluent guideline. The production figures provided must be based on actual daily production and not on design capacity or on predictions of future operations.

Item III

Self explanatory.

Item IV

Self explanatory.

Item V-A, B, and C

These items require you to collect and report data on the pollutants discharged for each of your outfalls. Each part of this item addresses a different set of pollutants and must be completed in accordance with the specific instructions for that part. The following general instructions apply to the entire item.

General Instructions

Part A requires you to report at least one analysis for each pollutant listed. Parts B and C require you to report analytical data in two ways. For some pollutants, you may be required to mark "X" in the "Testing Required" column, and test (sample and analyze) and report the levels of the pollutants in your discharge whether or not you expect them to be present in your discharge. For all others, you must mark "X" in either the "Believe Present" column or the "Believe Absent" column based on your best estimate, and test for those which you believe to be present. (See specific instructions on the form and below for Parts A through C.) Base your determination that a pollutant is present in or absent from your discharge on your knowledge of your raw materials, maintenance chemicals, intermediate and final products, and byproducts, and any previous analyses known to you of your effluent or similar effluent. (For example, if you manufacture pesticides, you should expect those pesticides to be present in contaminated storm water runoff.) If you would expect a pollutant to be present solely as a result of its presence in your intake water, you must mark "Believe Present" but you are not required to analyze for that pollutant.

A. Reporting. All levels must be reported as concentration and as total mass. You may report some or all of the required data by attaching separate sheets of paper instead of filling out pages 3 to 11 if the separate sheets contain all the required information. Use the following abbreviations in the columns headed "Units".

Concentration	Mass	
ppm parts per million mg/l milligrams per liter ppb	lbs pound	ls
ug/l micrograms per liter		

If you measure only one daily value, complete only the "Maximum Daily Values" columns and insert "1" into the "Number of Analyses" column. If requested you may be required to conduct additional analyses to further characterize your discharges. For composite samples, the daily value is the total mass or average concentration found in a composite sample taken over the operating hours of the facility during a 24-hour period; for grab samples, the daily value is the arithmetic or flow-weighted total mass or average concentration found in a series of at least four grab samples taken over the operating hours of the facility during a 24-hour period.

If you measure more than one daily value for a pollutant and those values are representative of your waste stream, you must report them. You also must determine the average of all values within the last year and report the concentration and mass under the "Long Term Average Values" columns and the total number of daily values under the "Number of Analyses" columns. Also, determine the average of all daily values taken during each calendar month, and report the highest average under the "Maximum 30-day Values" columns.

B. Sampling. The collection of samples for the reported analyses should be supervised by a person experienced in performing sampling of industrial wastewater. Any specific requirements contained in the applicable analytical methods must be followed for sample containers, sample preservation, holding times, the collection of duplicate samples, etc. The time when you sample should be representative of your normal operation, to the extent feasible, with all processes which contribute wastewater in normal operation, and with your treatment system operating properly with no system upsets. Samples must be collected during dry weather when the discharge is not influenced by storm water runoff. Samples should be collected from the center of the flow channel, where turbulence is at a maximum, at a site specified in your present permit, or at any site adequate for the collection of a representative sample.

For pH, temperature, cyanide, total phenols, residual chlorine, oil and grease, the volatile organics fraction of the GC/MS, and *Escherichia coli* (E. coli), grab samples must be used. For all other pollutants 24-hour composite samples must be used. However, a minimum of one grab sample may be taken for effluents from holding ponds or other impoundments with a retention period of greater than 24 hours. The Director may waive composite sampling for any outfall for which you demonstrate that use of an automatic sampler is infeasible and that a minimum of four grab samples will be representative of your discharge.

Data from samples taken in the past may be used, provided that:

- (i) All data requirements are met;
- (ii) Sampling was done no more than three years before submission; and
- (iii) All data are representative of the present discharge.
- (iv) Among the factors which would cause the data to be unrepresentative are significant changes in production level, changes in raw materials, processes, or final products, and changes in wastewater treatment. The Director may request additional information, including current quantitative data, if she or he determines it to be necessary to assess your discharges.
- C. Analysis: You must use test methods promulgated in 40 CFR Part 136; however, if none has been promulgated for a particular pollutant, you may use any suitable method for measuring the level of the pollutant in your discharge. Samples collected after October 1, 1996 must be analyzed by a laboratory certified in the State of Iowa to perform the required analysis except for pH, residual chlorine, dissolved oxygen, settleable solids and other pollutants that must be analyzed immediately upon collection of the sample. If you have two or more substantially identical outfalls, you may request permission to sample and analyze only one outfall and submit the results of the analysis for other substantially identical outfalls. If your request is granted, on a separate sheet attached to the application form, identify which outfall you did test, and describe why the outfalls which you did not test are substantially identical to the outfall which you did test.
- **D.** Reporting of Intake Data: If you wish to demonstrate your eligibility for a "net" effluent limitation for one or more pollutants, that is, an effluent limitation adjusted by subtracting the average level of the pollutant(s) present in your intake water you must report the results of at least one analysis of your raw water for the pollutant(s). NPDES regulations allow net limitations only in certain circumstances. To demonstrate your eligibility, on a separate sheet of paper, report the average of the results of analyses on your intake water (if your water is treated before use, test the water after it is treated) and discuss the requirements for a net limitation with your permitting authority.

PART V-A

Part V-A must be completed by all applicants for all outfalls, including outfalls containing only noncontact cooling water. However, at your request, the Director may waive the requirements to test for one or more of these pollutants, upon a determination that available information is adequate to support issuance of the permit with less stringent reporting requirements for these pollutants.

Use composite samples for all pollutants in this Part, except use grab samples for pH and temperature. See discussion in General Instructions to Item V for definitions of the columns in Part A. The "Long Term Average Values" column and "Maximum 30-day Values" column are not compulsory but should be filled out if data are available.

PART V-B

Part V-B must be completed by all applicants for all outfalls, including outfalls containing only noncontact cooling water. You must report quantitative data if the pollutant(s) in question is limited in an effluent limitations guideline either directly or indirectly, but expressly through limitation on an indicator (e.g., use of TSS as an indicator to control the discharge of iron and aluminum). For other discharged pollutants you must provide quantitative data or explain their presence in your discharge. Use composite samples for all pollutants you analyze for in this part, except use grab samples for residual chlorine, oil and grease, and *Escherichia coli* (E. coli). The "Long Term Average Values" column and "Maximum 30-day Values" column are not compulsory but should be filled out if data are available.

PART V-C

Table 1 lists the 34 "primary" industry categories in the left-hand column. For each outfall, if any of your processes which contribute wastewater falls into one of those categories, you must mark "X" in the "Testing Required" column and test for (1) all of the toxic metals, cyanide, and total phenols, and (2) the organic toxic pollutants contained in Table 1 applicable to your category, unless you qualify as a small business (see below). The organic toxic pollutants are listed by GC/MS fractions on pages 6 to 11 in Part V-C. For example, the Organic Chemicals Industry has an "X" in all four fractions; therefore, applicants in this category must test for all organic toxic pollutants in Part V-C. The inclusion of total phenols in Part V-C is not intended to classify total phenols as a toxic pollutant. When you determine which industry category you are in to find your testing requirements, you are not determining your category for any other purpose and you are not giving up your right to challenge your inclusion in that category (for example, for deciding whether an effluent guideline is applicable) before your permit is issued. For all other cases (secondary industries, nonprocess wastewater outfalls, and nonrequired GC/MS fractions), you must mark "X" in either the "Believed Present" column or the "Believed Absent" column for each pollutant. For every pollutant you know or have reason to believe is present in your discharge in concentrations of 10 ppb or greater, you must report quantitative data. For acrolein, acrylonitrile, 2,4 dinitrophenol, and 2methyl-4, 6 dinitrophenol, where you expect these four pollutants to be discharged in concentrations of 100 ppb or greater, you must report quantitative data. For every pollutant expected to be discharged in concentrations less than the thresholds specified above, you must either submit quantitative data or briefly describe the reasons the pollutant is expected to be discharged. If you qualify as a small business (see below) you are exempt from testing for the organic toxic pollutants, listed on pages 6 to 11 in Part V-C. The "Long Term Average Values" column and "Maximum 30-day Values" column are not compulsory but should be filled out if data are available. You are required to mark "Testing Required" for dioxin if you use or manufacture one of the following compounds:

- (a) 2,4,5-trichlorophenoxy acetic acid, (2,4,5-T);
- (b) 2-(2,4,5-trichlorophenoxy) propanoic acid, (Silvex, 2,4,5-TP);
- (c) 2-(2,4,5-tricholorphenoxy) ethyl 2,2-dicholoropropionate, (Erbon);
- (d) O,O-dimethyl O-(2,4,5-tricholorphenyl) phosphorothioate, (Ronnel);
- (e) 2,4,5-tricholorphenol, (TCP); or
- (f) hexachlorophene, (HCP).

If you mark "Testing Required" or "Believed Present," you must perform a screening analysis for dioxins, using gas chromotography with an electron capture detector. A TCDD standard for quantitation is not required. Describe the results of this analysis in the space provided; for example, "no measurable baseline deflection at the retention time of TCDD" or "a measurable peak within the tolerances of the retention time of TCDD." The permitting authority may require you to perform a quantitative analysis if you report a positive result.

Small Business Exemption - If you are a "small business," you are exempt from the reporting requirements for the organic toxic pollutants listed in Part V-C. There are two ways in which you can qualify as a "small business":

- i. If your facility is a coal mine, and if your probable total annual production is less than 100,000 tons per year, you may submit past production data or estimated future production (such as a schedule of estimated total production under 30 CFR 795.14(c)) instead of conducting analyses for the organic toxic pollutants.
- ii. If your facility is not a coal mine, and if your gross total annual sales for the most recent three years average less than \$100,000 per year (in second quarter 1980 dollars), you may submit sales data for those years instead of conducting analyses for the organic toxic pollutants.

The production or sales data must be for the facility which is the source of the discharge. The data should not be limited to production or sales for the process or processes which contribute to the discharge, unless those are the only processes at your facility. For sales data, in situations involving intracorporate transfer of goods and services, the transfer price per unit should approximate market prices for those goods and services as closely as possible. Sales figures for years after 1980 should be indexed to the second quarter of 1980 by using the gross national product price deflator (second quarter of 1980=100). This index is available in National Income and Product Accounts of the United States (Department of Commerce, Bureau of Economic Analysis)

TABLE 1
TESTING REQUIREMENTS FOR ORGANIC PRIORITY POLLUTANTS

40 CFR	ILBINO REQUIREMENTS FOR ON	Production			MS Fraction	S
Part	Industry Category	Based				
Number	, ,	Guideline	Volatile	Acid	Base/Neutr	Pesticide
					al	
456	Adhesives and sealants		X	X	X	-
467	Aluminum forming	*	X	X	X	-
444	Auto and other laundries		X	X	X	X
461	Battery manufacturing	*	X	-	X	-
465	Coil coating		X	X	X	-
468	Copper forming		X	X	X	-
469	Electrical and electronic components		X	X	X	X
413	Electroplating		X	X	X	-
457	Explosives manufacturing		-	X	X	-
433	Metal finishing		X	X	X	-
464	Metal molding and casting	*	X	X	X	-
454	Gum and wood chemical manufacturing		X	X	-	-
	(Except subparts D and F)					
	Subpart D - tall oil rosin		X	X	X	-
	Subpart F - rosin-based derivatives		X	X	X	-
415	Inorganic chemicals manufacturing		X	X	X	-
420	Iron and steel manufacturing	*	X	X	X	-
425	Leather tanning and finishing	*	X	X	X	-
471	Nonferrous metals forming		X	X	X	X
440	Ore mining and dressing		-	X	-	-
414	Organic chemicals, plastics and synthetic fibers		X	X	X	X
447	Paint formulating		X	X	X	-
446	Ink formulating		X	X	X	-
455	Pesticide chemicals	*	X	X	X	X
419	Petroleum refining		X	_	_	_
439	Pharmaceutical preparations		X	X	X	-
459	Photographic equipment and supplies		X	X	X	-
463	Plastics molding and forming		X	-	-	_
448	Printing and publishing		X	X	X	X
430	Pulp, paper and paperboard		=	-	-	-
428	Rubber processing		X	X	X	_
417	Soap and detergent manufacturing		X	X	X	-
423	Steam electric power plants	*	X	X	-	_
410	Textile mills (except Subpart C)		X	X	X	_
429	Timber products processing		X	X	0	X
	Subpart A		0	X	0	0
	Subparts B, C, D, R		0	X	0	0
	Subpart E		X	X	0	X
	Subparts F, G, H, I, K		X	X	0	0
	Subparts I, G, H, I, K Subparts L, M, N, O, P		X	X	0	0
	Subparts J, U		X	X	X	0
	Subparts Q, S, T		X	X	0	X
<u> </u>	Subparts Q, S, 1		Λ	Λ		Λ

^{*} A production based effluent guideline has been promulgated by EPA in accordance with Section 402 of the Clean Water Act

GC/MS = Gas Chromatography/Mass Spectrometry

X = Testing required

- = Testing not required

O = Testing required only if believed present

TABLE 2 HAZARDOUS SUBSTANCES

1. Acetaldehyde 2. Acetic acid 3. Acetic anhydride 4. Acetone cyanohydrin 5. Acetyl bromide 6. Acetyl chloride 7. Acrolein 8. Acrylonitrile 9. Adipic acid 10. Aldrin 11. Allyl alcohol 12. Allyl chloride 13. Aluminum sulfate 14. Ammonia 15. Ammonium acetate 16. Ammonium benzoate 17. Ammonium bicarbonate 18. Ammonium bichromate 19. Ammonium biflouride 20. Ammonium bisulfate 21. Ammonium carbamate 22. Ammonium carbonate 23. Ammonium chloride 24. Ammonium chromate 25. Ammonium citrate 26. Ammonium fluroborate 27. Ammonium fluoride 28. Ammonium hydroxide 29. Ammonium oxalate 30. Ammonium silicofluoride 31. Ammonium sulfamate 32. Ammonium sulfide 33. Ammonium sulfite 34. Ammonium tartrate 35. Ammonium thiocyanate 36. Ammonium thiosulfate 37. Amvl acetate 38. Aniline 39. Antimony pentachloride 40. Antimony potassium tartrate 41. Antimony tribromide 42. Antimony trichloride 43. Antimony trifluoride 44. Antimony trioxide 45. Arsenic disulfide 46. Arsenic pentoxide 47. Arsenic trichloride 48. Arsenic trioxide 49. Arsenic trisulfide

50. Barium cyanide

51. Benzene 52. Benzoic acid 53. Benzonitrile 54. Benzovl chloride 55. Benzyl chloride 56. Beryllium chloride 57. Beryllium fluoride 58. Beryllium nitrate 59. Butylacetate 60. n-Butylphthalate 61. Butylamine 62. Autryic acid 63. Cadmium acetate 64. Cadmium bromide 65. Cadmium chloride 66. Calcium arsenate 67. Calcium arsenite 68. Calcium carbide 69. Calcium chromate 70. Calcium cyanide 71. Calcium dodecylbenzenesulfonate 72. Calcium hypochlorite 73. Captan 74. Carbaryl 75. Carbofuran 76. Carbon disulfide 77. Carbon tetrachloride 78. Chlordane 79. Chlorine 80. Chlorobenzene 81. Chloroform 82. Chlorpyrifos 83. Chlorosulfonic acid 84. Chromic acetate 85. Chromic acid 86. Chromic sulfate 87. Chromous chloride 88. Cobaltous chloride 89. Cobaltus bromide 90. Cobaltous formate 91. Coumaphos 92. Cresol 93. Crotonaldehyde 94. Cupric acetate 95. Cupric acetoarsenite 96. Cupric chloride 97. Cupric nitrate 98. Cupric oxalate 99. Cupric sulfate 100. Cupric sulfate ammoniated

101. Cupric tartrate 102. Cyanogen chloride 103. Cyclohexane 104. 2.4-D acid (2.4-Dichlorophenoxyacetic acid) 105. 2,4-D esters (2,4,-Dichlorophenoxyacetic acid esters) 106. DDT 107. Diazanon 108. Dicamba 109. Dichlobenil 110. Dichlone 111. Dichlorobenzene 112. Dichloropropane 113. Dichloropropene 114. Dichloropropene-dichloropropane mix 115. 2,2-Dichloropropionic acid 116. Dichlorvos 117. Dieldrin 118. Diethylamine 119. Dimethylamine 120. Dinitrobenzene 121. Dinitrophenol 122. Dinitrotoluene 123. Diquat 124. Disulfoton 125. Diuron 126. Dodecylbenzenesulfonic acid 127. Endosulfan 128. Endrin 129. Epichlorohydrin 130. Ethion 131. Ethylbenzene 132. Ethylenediamine 133. Ethylene dibromide 134. Ethylene dichloride 135. Ethylene diaminetetracetic acid (EDTA) 136. Ferric ammonium citrate 137. Ferric ammonium oxalate 138. Ferric chloride 139. Ferric fluoride 140. Ferric nitrate 141. Ferric sulfate 142. Ferrous ammonium sulfate 143. Ferrous chloride 144. Ferrous sulfate 145. Formaldehyde 146. Formic acid 147. Fumaric acid 148. Furfural 149. Guthion

150. Heptachlor

TABLE 2 HAZARDOUS SUBSTANCES

151. Hexachlorocyclopentadiene	201.	Nitrophenol	251. Sulfuric acid
152. Hydrochloric acid		Nitrotoluene	252. Sulfur monochloride
153. Hydrofluoric acid		Paraformaldehyde	253. 2,4,5-T acid (2,4,5-
154. Hydrogen cyanide		Parathion	Trichlorophenoxyacetic acid)
155. Hydrogen sulfide		Pentachlorophenol	254. 2,4,5-T amines (2,4,5-
156. Isoprene		Phenol	Trichlorophenoxyacetic acid amines)
157. Isopropanolamine		Phosgene	255. 2,4,5-T esters (2,4,5-
dodecylbenzenesulfonate		Phosphoric acid	Trichlorophenoxyacetic acid esters)
158. Kelthane		Phosphorus	256. 2,4,5-T salts (2,4,5-
159. Kepone		Phosphorus oxychloride	Trichlorophenoxyaceticacid salts)
160. Lead acetate		Phosphorus pentasulfide	257. 2,4,5-TP acid (2,4,5-
161. Lead arsenate		Phosphorus trichloride	Trichlorophenoxy propanoic acid)
162. Lead chloride	213.	Polychlorinated biphenyls (pcb's)	258. 2,4,5-TP esters (2,4,5-
163. Lead fluoroborate		Potassium arsenate	Trichlorophenoxy propanoic esters)
164. Lead fluoride	215.	Potassium arsenite	259. TDE (Tetrachlorodiphenyl ethane)
165. Lead iodide	216.	Potassium bichromate	260. Tetraethyl lead
166. Lead nitrate	217.	Potassium chromate	261. Tetraethyl pyrophosphate
167. Lead strearate	218.	Potassium cyanide	262. Thallium sulfate
168. Lead sulfate	219.	Potassium hydroxide	263. Toluene
169. Lead sulfide	220.	Potassium permanganate	264. Toxaphene
170. Lead thiocyanate	221.	Propargite	265. Trichlorofon
171. Lindane	222.	Propionic acid	266. Trichloroethylene
172. Lithium chromate	223.	Propionic anhydride	267. Trichlorophenol
173. Malathion	224.	Propylene oxide	268. Triethanolamine
174. Maleic acid	225.	Pyrethrins	dodecylbenzenesulfonate
175. Maleic anhydride		Quinoline	269. Triethlamine
176. Mercaptodimethur		Resorcinol	270. Trimethylamine
177. Mercuric cyanide	228.	Selenium oxide	271. Uranyl acetate
178. Mercuric nitrate		Silver nitrate	272. Uranyl nitrate
179. Mercuric sulfate		Sodium	273. Vanadium pentoxide
180. Mercuric thiocyanate		Sodium arsenate	274. Vanadyl sulfate
181. Mercurous nitrate		Sodium arsenite	275. Vinyl acetate
182. Methoxychlor		Sodium bichromate	276. Vinylidene chloride
183. Methyl mercaptan		Sodium bifluoride	277. Xylene
184. Methyl methacrylate		Sodium bisulfite	278. Xylenol
185. Methyl parathion		Sodium chromate	279. Zinc acetate
186. Mevinphos		Sodium cyanide	280. Zinc ammonium chloride
187. Mexacarbate		Sodium dodecylbenzenesulfonate	281. Zinc borate
188. Monoethylamine		Sodium fluoride	282. Zinc bromide
189. Monomethylamine 190. Naled		Sodium hydroxida	283. Zinc carbonate 284. Zinc chloride
		Sodium hydroxide Sodium hypochlorite	
191. Naphthalene		Sodium nypochiorne Sodium methylate	285. Zinc cyanide 286. Zinc fluoride
192. Naphthenic acid193. Nickel ammonium sulfate		Sodium nitrite	287. Zinc formate
194. Nickel chloride		Sodium phosphate (dibasic)	288. Zinc hydrosulfide
195. Nickel hydroxide		Sodium phosphate (tribasic)	289. Zinc nitrate
196. Nickel nitrate		Sodium selinite	290. Zinc phenolsulfonate
197. Nickel sulfate		Strontium chromate	291. Zinc phosphide
198. Nitric acid		Strychnine	292. Zinc silicofluoride
199. Nitrobenzene		Styrene	293. Zinc sulfate
200. Nitrogen dioxide	250.	51,10110	294. Zirconium nitrate
200. Tittingen diomae			295. Zirconium potassium fluoride
			296. Zirconium sulfate
			207 Zine animum tetra eleleni de

297. Zirconium tetrachloride